



Ningbo Realpower Magnetic Industry Co.,Ltd.

Magnetizer-High-Voltage Series

1,000-2,000V series

FOR MULTIPLE POLES MAGNETIZATION OF ALL KINDS MAGNET ESPECIALLY, DC MICRO MOTOR ASSEMBLY BY MULTIPLE POLE OF RARE- EARTH MAGNET OR FERRITE MAGNET.

MD- ---- D: Demagnetizer C: Super Current N: Normal Current
X100V X100uF

Spec/Model	MD1010	MD1020	MD1510	MD1520	MD2010	MD2020
input power supply	AC220V 20A	AC220V 30A	AC220V 30A	AC220V 30A	AC220V 30A	AC220V 30A
output voltage	DC100-2500V	DC100-1000V	DC100-1500V	DC100-1500V	100-2000V	DC100-2000V
output current	3KA-30KA	5KA-20KA	5KA-20KA	5KA-20KA	5KA-30KA	5KA-30KA
Electrostatic capacity	1000 uF	2000 uF	2000 uF	2000 uF	2000 uF	2000 uF
charging time	1-10 sec	1-15 sec	2-20 sec	2-25 sec	3-35 sec	3-35 sec
cycle used	2-20 sec	2-25 sec	3-30 sec	3-35 sec	4-45 sec	4-45 sec
weight	150kg	150kg	150kg	170kg	160kg	180kg
Dimensions H X W X L	600X700X1400	600X700X1400	600X700X1400	600X700X1400	600X700X1400	600X700X1400
CUSTOM SPECIAL SPECIFICATION ACCEPTABLE						

2,500-3,500V series

FOR LARGE SIZE MAGNETS MAGNETIZATION THE BEST EQUIPMENT FOR WHOLE SIZE RING TYPE AND ARC SEGMENT OF FERRITE OF RARE-EARTH MAGNET, SINGLE POLE; MULTIPLE POLES AXIAL OR RADIUS MAGNETIZATION.

MD- ---- D: Demagnetizer C: Super Current N: Normal Current
X100V X100uF

Spec/Model	MD2510	MD2520	MD3020	MD3030	MD3520	MD3540
input power supply	AC220V 40A	AC220V 50A	AC220V 50A	AC220V 75A	AC220V 60A	AC220V 80A
output voltage	DC100-2500V	DC100-2500V	DC100-3000V	DC100-3000V	DC100-3500V	DC100-3500V
output current	3KA-30KA	3KA-30KA	3KA-30KA	3KA-30KA	3KA-30KA	3KA-30KA
Electrostatic capacity	1000 uF	2000 uF	2000 uF	3000 uF	2000 uF	4000 uF
charging time	5-20 sec	7-25 sec	8-30 sec	10-30 sec	15-35 sec	20-35 sec
cycle used	6-30 sec	8-35 sec	9-40 sec	11-40 sec	16-50 sec	21-50 sec
weight	250kg	460kg	500kg	600kg	600kg	720kg
Dimensions H X W X L	700X600X900	1000X800X1800	1000X800X1800	1300X800X1800	1000X800X1800	1600X800X1800
CUSTOM SPECIAL SPECIFICATION ACCEPTABLE						



Magnetizer LV